



MINIMUM EXCAVATION SIZE:  
6'-2" x 10'-0" x DEPTH REQUIRED.

■ ILLUSTRATION IS TYPICAL ONLY OF GENERAL SERIES CONFIGURATION: FOR SPECIFIC CONFIGURATION, CALL JENSEN PRECAST.

- (A) 66" TOP SECTION WT.= 10,880 Lbs.
- (B) 12" EXTENSION SECTION (OPTIONAL) WT.= 1,770 Lbs.
- (C) BASE SLAB WT.= 3,300 Lbs.
- (D) 18" x 44" DEEP DUCT KNOCKOUT SHOWN
- (E) 12" DIA. SUMP KNOCKOUT
- (F) 9" x 18" KNOCKOUT - TWO EACH SIDE
- (G) FOR COVERS: SEE COVER AND NECKING SECTION.
- (H) PULL IRONS (FLUSH)

- DESIGN FOR H-20-44 BRIDGE LOADING.
- ASSEMBLY TO BE PLACED ON A 6" BASE OF CRUSHER RUN FOR EASE OF INSTALLATION AND EVEN LOAD DISTRIBUTION.
- MINIMUM HEADROOM IS 5'-6". ADDITIONAL DEPTHS ARE AVAILABLE BY EXTENSION SECTIONS.

<b>4'-0" x 6'-6" x 5'-6"</b> <b>MANHOLE / VAULT</b>	
ORG. DWG. DATE <b>08-01-04</b>	REV. DWG. DATE

**JENSEN**  
PRECAST

**466 SERIES**