


**MINIMUM EXCAVATION SIZE:
8'-0" x 11'-6" x DEPTH REQUIRED.**



■ ILLUSTRATION IS TYPICAL ONLY OF GENERAL SERIES CONFIGURATION: FOR SPECIFIC CONFIGURATION, CALL JENSEN PRECAST.

- (A) TOP SECTION WT.= 13,200 Lbs.
- (B) BOTTOM SECTION WT.= 11,300 Lbs.
- (C) SUMP - VARIOUS SIZES AVAILABLE
- (D) KNOCKOUT - VARIOUS SIZES AVAILABLE
- (E) FOR COVERS: SEE COVER AND NECKING SECTION.
- (F) TERMINATORS - VARIOUS SIZES AVAILABLE
- (G) DEEP DUCT (SHOWN) FLAT WALL AVAILABLE
- (H) PULL IRON (FLUSH)

■ DESIGN FOR H-20-44 BRIDGE LOADING.

■ ASSEMBLY TO BE PLACED ON A 6" BASE OF CRUSHER RUN FOR EASE OF INSTALLATION AND EVEN LOAD DISTRIBUTION.

6'-0" x 8'-0" x 7'-0" MANHOLE / VAULT		JENSEN PRECAST
<small>ORG. DWG. DATE 11-15-00</small>	<small>REV. DWG. DATE</small>	
		68 SERIES