



MINIMUM EXCAVATION SIZE:
3'-8" x 5'-2" x DEPTH REQUIRED.

■ ILLUSTRATION IS TYPICAL ONLY OF GENERAL SERIES CONFIGURATION: FOR SPECIFIC CONFIGURATION, CALL JENSEN PRECAST.

- (A) 6" TOP SECTION WT.= 230 Lbs.
- (B) 6" EXTENSION SECTION (OPTIONAL NOT SHOWN)
- (C) BOTTOM SECTION WT.= 2,100 Lbs.
- (D) 20" x 20" KNOCKOUT - EACH END
- (E) 8" x 16" KNOCKOUT - TWO EACH SIDE
- (F) 6" DIA. SUMP KNOCKOUT
- (G) FOR COVERS: SEE COVER AND NECKING SECTION.
- (H) PULL IRON

- DESIGNED FOR PEDESTRIAN OR LIGHT TRAFFIC LOADING.
- ASSEMBLY TO BE PLACED ON A 6" BASE OF CRUSHER RUN FOR EASE OF INSTALLATION AND EVEN LOAD DISTRIBUTION.
- MINIMUM HEADROOM IS 3'-0". ADDITIONAL DEPTHS ARE AVAILABLE BY EXTENSION SECTIONS.

2'-6" x 4'-0" VARIABLE
DEPTH FLATWALL
PULL BOX



3048 FPB

ORG. DWG. DATE 10-24-00	REV. DWG. DATE
----------------------------	----------------