


MINIMUM EXCAVATION SIZE:
VAR. x VAR. x DEPTH REQUIRED.



■ ILLUSTRATION IS TYPICAL ONLY OF GENERAL SERIES CONFIGURATION: FOR SPECIFIC CONFIGURATION, CALL JENSEN PRECAST.

- (A) TOP SLAB
- (B) 2 PC. BOTTOM SLAB (1 PC. AVAILABLE)
- (C) SIDE PANEL
- (D) END PANEL
- (E) SUMP - VARIOUS SIZES AVAILABLE
- (F) PULL IRON (FLUSH)
- (G) FOR COVERS: SEE COVER AND NECKING SECTION.
- (H) BOLT-UP CASTINGS

■ DESIGN FOR H-20-44 BRIDGE LOADING.

■ ASSEMBLY TO BE PLACED ON A 6" BASE OF CRUSHER RUN FOR EASE OF INSTALLATION AND EVEN LOAD DISTRIBUTION.

■ 6'-0" X 10'-0" PANEL VAULT SHOWN.

VAR. WIDTH x VAR. LENGTH x VAR. DEPTH PANEL VAULT		 PANEL VAULT SERIES
<small>ORG. DWG. DATE</small> 11-15-00	<small>REV. DWG. DATE</small>	