## **NO 9 PULLBOX** COVER MARKED "ADOT ELEC-3'-6"x3'-6"x3'-2" HIGH VOLTAGE' (NOMINAL INSIDE DIMENSIONS) **ADOT SIGNAL & LIGHTING** PB9-ADOT-I 36"x36" GALVANIZED SPRING ASSISTED COVER WITH 180° LAYBACK HINGE AND RECESSED PADLOCK BOX RECESSED HANDLE, PENTAHEAD LOCKING BOLTS. CAST IN FLUSH CENTERED IN SLAB 4' - 0'24" STRUT CAST INTO WALLS-4 TOTAL ·6" PULLING IRONS 3'-8" 4 TOTAL 18"x18" THINWALL KNOCKOUTS EACH WALL 4 TOTAL

DESIGN LOAD: INCIDENTAL H-20 DESIGN FOR 16,000 LB WHEEL LOAD WITHOUT IMPACT, IN AREAS OF LOW SPEED INTERMITTENT TRAFFIC ONLY; NOT FOR HIGH DENSITY TRAFFIC.

WATER TABLE ASSUMED TO BE BELOW BOTTOM OF STRUCTURE.

4'-0'

FOR COMPLETE DESIGN AND PRODUCT INFORMATION CONTACT JENSEN PRECAST.



4'-0"

9" DIA. SUMP