



MINIMUM EXCAVATION SIZE:
10'-0" x 10'-0" x DEPTH REQUIRED.

■ ILLUSTRATION IS TYPICAL ONLY OF GENERAL SERIES CONFIGURATION; FOR SPECIFIC CONFIGURATION, CALL JENSEN PRECAST.

- Ⓐ TOP SECTION (8'-0" MAX)
- Ⓑ BOTTOM SECTION (8'-0" MAX)
- Ⓒ KNOCKOUT OR TERMINATORS AS REQUIRED.
- Ⓓ SUMP - VARIOUS SIZES AVAILABLE.

- DESIGN FOR H-20-44 BRIDGE LOADING.
- MANHOLE COVERS AND NECKING: SEE DRAWINGS IN THE COVERS AND NECKING SECTION.
- ASSEMBLY TO BE PLACED ON A 6" BASE OF CRUSHER RUN FOR EASE OF INSTALLATION AND EVEN LOAD DISTRIBUTION.
- MINIMUM HEADROOM IS 6'-0". ADDITIONAL DEPTHS ARE AVAILABLE.

8'-0" x 8'-0" VARIABLE
DEPTH FLAT WALL
MANHOLE

JENSEN
PRECAST®

88 SERIES

ORG. DWG. DATE
10-24-00

REV. DWG. DATE