



■ ILLUSTRATION IS TYPICAL ONLY OF GENERAL SERIES CONFIGURATION: FOR SPECIFIC CONFIGURATION, CALL JENSEN PRECAST.

MINIMUM EXCAVATION SIZE:
4'-8" x 9'-8" x DEPTH REQUIRED.

- (A) 12" TOP SECTION WT.= 996 Lbs.
- (B) 12" EXTENSION SECTION (OPTIONAL NOT SHOWN)
- (C) BOTTOM SECTION WT.= 4,415 Lbs.
- (D) 14" X 18" X 12" DEEP DUCT KNOCKOUT EACH END
- (E) 12" x 18" KNOCKOUT - TWO EACH SIDE
- (F) 12" DIA. SUMP KNOCKOUT
- (G) FOR COVERS: SEE COVER AND NECKING SECTION.
- (H) PULL IRON

- DESIGNED FOR PEDESTRIAN OR LIGHT TRAFFIC LOADING.
- ASSEMBLY TO BE PLACED ON A 6" BASE OF CRUSHER RUN FOR EASE OF INSTALLATION AND EVEN LOAD DISTRIBUTION.
- MINIMUM HEADROOM IS 4'-0". ADDITIONAL DEPTHS ARE AVAILABLE BY EXTENSION SECTIONS.

3'-0" x 6'-0" VARIABLE DEPTH PULL BOX		JENSEN PRECAST®
3672 DPB		
ORG. DWG. DATE 10-24-00	REV. DWG. DATE	